Image shown may not reflect actual package.

- The Cat® S•O•S℠ program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

STANDBYMission Critical Standby

1400 ekW 1750 kVA 50 Hz 1500 rpm 400 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY
- Low Emissions

DESIGN CRITERIA
- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

FULL RANGE OF ATTACHMENTS
- Wide range of bolt-on system expansionattachments, factory designed and tested
- Flexible packaging options for easy and costeffective installation

SINGLE-SOURCE SUPPLIER
- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT
- Cat dealers provide extensive post sale supportincluding maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch storesoperating in 200 countries

CAT® 3512B-HD TA DIESEL ENGINE
- Reliable, rugged, durable design
- Field-proven in thousands of applicationsworldwide
- Four-stroke-cycle diesel engine combinesconsistent performance and excellent fuel economy with minimum weight

CAT GENERATOR
- Matched to the performance and outputcharacteristics of Cat engines
- Industry leading mechanical and electrical design
- Industry leading motor starting capabilities
- High Efficiency

CAT EMCP 4 CONTROL PANELS
- Simple user friendly interface and navigation
- Scalable system to meet a wide range ofcustomer needs
- Integrated Control System and Communications Gateway

DIESEL GENERATOR SET

FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	• Air cleaner	
Cooling	• Package mounted radiator	

Mission Critical Standby 1400 ekW 1750 kVA

STANDBY1400ekW1750kVA

50 Hz 1500 rpm 400 Volts

Exhaust	• Exhaust flange outlet	[ ] Exhaust mufflers (except Tier 4)
Fuel	• Primary fuel filter with integral water separator • Secondary fuel filters • Fuel priming pump	
Generator	• Matched to the performance and outputcharacteristics of Cat engines • Load adjustment module provides engine relief uponload impact and improves laod acceptance and recovery time • IP23 protection	[ ] Oversize and premium generators [ ] Permanent magnet excitation (PMG) [ ] Internal excited (IE) [ ] Anti-condensation space heaters
Power Termination	• Bus bar	[ ] Circuit breakers, UL listed [ ] Circuit breakers, IEC compliant
Control Panel	• EMCP 4 Genset Controller	[ ] EMCP 4.2 [ ] EMCP 4.3 [ ] EMCP 4.4 [ ] Generator temperature monitoring and protection [ ] Load share module [ ] Digital I/O module [ ] Remote monitoring software
Mounting		[ ] Rubber vibration isolators
Starting/Charging		[ ] Battery chargers [ ] Oversize batteries [ ] Jacket water heater [ ] Heavy duty starting system [ ] Charging alternator [ ] Air starting motor with control and silencer (3500 & C175 models only)
General	• Paint - Caterpillar Yellow except rails and radiators gloss black	The following options are based on regional and product configuration: [ ] Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007 [ ] EU Certificate of Conformance (CE) [ ] UL 2200 package [ ] CSA Certification [ ] EEC Declaration of Conformity [ ] Enclosures- sound attenuated, weather protective [ ] Automatic transfer switches (ATS) [ ] Integral & sub-base fuel tanks [ ] Integral & sub-base UL listed dual wall fuel tanks

SPECIFICATIONS

STANDBY1400ekW1750kVAMission Critical Standby 1400 ekW 1750 kVA

50 Hz 1500 rpm 400 Volts

CAT GENERATOR

Cat Generator
Frame size..... 1602
Excitation.....Internal Excitation
Pitch.....0.6667
Number of poles.....4
Number of bearings..... 2
Number of Leads.....006
Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion
- Consult your Caterpillar dealer for available voltages
IP Rating.....IP23
Alignment.....Closed Coupled
Overspeed capability.....150
Wave form Deviation (Line to Line)..... 002.00 Voltage regulator.....3 Phase sensing with selectible volts/Hz
Voltage regulation.....Less than +/- 1/2% (steady state) Less than +/- 1% (no load to full load)

CAT DIESEL ENGINE

3512B-HD TA, V-12, 4-Stroke Water-cooled Diesel
Bore.....170.00 mm (6.69 in)
Stroke.....215.00 mm (8.46 in)
Displacement.....58.56 L (3573.55 in^3)
Compression Ratio.....15.5:1
Aspiration.....TA
Fuel System..... Electronic unit injection
Governor Type.....ADEM3

CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions Digital indication for:
- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence - Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVAr) (32RV)
- Overcurrent (50/51) Communications:
- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton Compatible with the following:
- Digital I/O module - Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

STANDBY1400ekW1750kVAMission Critical Standby 1400 ekW 1750 kVA

50 Hz 1500 rpm 400 Volts

TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM8239	
Low Emissions		
Generator Set Package Performance		
Genset Power rating @ 0.8 pf	1750 kVA	
Genset Power rating with fan	1400 ekW	
Fuel Consumption		
100% load with fan	371.7 L/hr	98.2 Gal/hr 74.1
75% load with fan	280.4 L/hr	Gal/hr
50% load with fan	193.2 L/hr	51.0 Gal/hr
Cooling System[1]		
Air flow restriction (system)	0.12 kPa	0.48 in. water
Engine Coolant capacity with radiator/exp. tank	305.8 L	80.8 gal 41.4
Engine coolant capacity	156.8 L	gal
Radiator coolant capacity	149.0 L	39.4 gal
Inlet Air		
Combustion air inlet flow rate	128.1 m^3/min	4523.8 cfm
Exhaust System		
Exhaust stack gas temperature	444.0 º C	831.2 º F
Exhaust gas flow rate	323.0 m^3/min	11406.6 cfm
Exhaust flange size (internal diameter)	203.2 mm	8.0 in
Exhaust system backpressure (maximum allowable)	6.7 kPa	26.9 in. water
Heat Rejection		
Heat rejection to coolant (total)	514 kW	29231 Btu/min
Heat rejection to exhaust (total)	1383 kW	78651 Btu/min
Heat rejection to aftercooler	417 kW	23715 Btu/min
Heat rejection to atmosphere from engine	121 kW	6881 Btu/min
Heat rejection to atmosphere from generator	69.0 kW	3924.0 Btu/min
Alternator[2]		
Motor starting capability @ 30% voltage dip	4266 skVA	
Frame	1602	
Temperature Rise	125 º C	225 º F
Lube System		
Sump refill with filter	310.4 L	82.0 gal
Emissions (Nominal)[2]		
NOx mg/nm3	1709.3 mg/nm^3	
CO mg/nm3	317.9 mg/nm^3	
HC mg/nm3	72.5 mg/nm^3	
PM mg/nm3	31 mg/nm^3	

[1] For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory. [2] UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

[2] Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77ºF, 28.42 in HG and number 2 diesel fuel with 35º API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

STANDBY1400ekW1750kVAMission Critical Standby 1400 ekW 1750 kVA

50 Hz 1500 rpm 400 Volts

RATING DEFINITIONS AND CONDITIONS

Applicable Codes and Standards: AS1359, CSA C22.2 No 100-04, UL142, UL489, UL601, UL869, UL2200, NFPA 37, NFPA 70, NFPA 99, NFPA 110, IBC, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, 72/23/EEC, 98/37/EC, 2004/108/EC

StandbyMission Critical Standby - Output available with varying load for the- Output available with varying

duration of the interruption of the normal source power.load for the duration of the interruption of the normal source power. Average power output is 85% of the

Average power output is 70% of the standby power standby power rating. Typical peak demand up to 100% rating. Typical operation is 200 hours per year, with of standby rated ekW for 5% of the operating time.

maximum expected usage of 500 hours per year.Typical operation is 200 hours per year, with maximum

expected usage of 500 hours per year. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

Ratings are based on SAE J1349 standard conditions.

These ratings also apply at ISO3046 standard conditions. **Fuel Rates** are based on fuel oil of 35º API (16º C or 60º F) gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29º C (85º F) and weighing 838.9 g/liter

(7.001 lbs/U.S. gal.).

Additional Ratings may be available for specific customer requirements. Consult your Cat representative for details.

DIMENSIONS

Package Dimensions	
Length	**Information not available at this time.**
Width	
Height	

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2336966).

STANDBY1400ekW1750kVAMission Critical Standby 1400 ekW 1750 kVA

50 Hz 1500 rpm 400 Volts

Performance No.: DM8239

Feature Code: 512DE6Y

Gen. Arr. Number: 2523838

Source: European Sourced

March 04 2013 21511074

www.Cat-ElectricPower.com

2013 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.